

Finance Department  
Purchasing Division

**REQUEST FOR PROPOSALS (RFP)  
Specification No. 20-11345-C  
FOR  
FY20 Sidewalk Inspection & Shaving Services  
PROPOSALS WILL NOT BE OPENED AND READ PUBLICLY**

**ADDENDUM "A"**  
9/6/2019

Dear Proposer:

The following amendments are hereby made to the subject document. (Attached)


**Proposals/bids must be received no later than 2:00 pm, on Thursday, September 19, 2019.** All responses must be in a sealed envelope and have "**FY20 Sidewalk Inspection & Shaving Services**" and **Specification No.20-11345-C** clearly marked on the **outer most mailing envelope**.

**Mail or Hand Deliver To:**  
City of Berkeley  
Finance Department/General Services Division  
2180 Milvia Street, 3rd Floor  
Berkeley, CA 94704

Proposals/bids will not be accepted after the date and time stated above. Incomplete bids that do not conform to the requirements specified herein will not be considered.

Thank you for your interest in working with the City of Berkeley for this service. We look forward to receiving your response.

Sincerely,



Dennis Dang  
Acting General Services manager

## **Addendum “A”**

### Questions and Answers for Specification No. 20-1345-C FY20 Sidewalk Inspection & Shaving Services

The City of Berkeley has amended the subject documents from the following scope of service:

1. **Scope of Services:**

**Delete:**

**2. Concrete Shaving: a.** All specified locations shall be shaved to provide a smooth transition between sidewalk concrete panels/slabs. The shaved areas shall be uniform, smooth, with minimal grooving, and straight at the backline with little or no scarring of the adjacent concrete. The maximum longitudinal slope of shaving is 20:1 (5%), in addition to a non-slip finish.

**REPLACE with the following text:**

**2. Concrete Shaving: a.** All specified locations shall be shaved to provide a smooth transition between sidewalk concrete panels/slabs. The shaved areas shall be uniform, smooth, with minimal grooving, and straight at the backline with little or no scarring of the adjacent concrete. The maximum longitudinal slope of shaving is **12:1 (8.33%)**, in addition to a non-slip finish.

Except as provided herein all other terms and conditions remain unchanged.